


Features

- Pb free product — RoHS compliant
- Low power consumption, High efficiency
- Reliable and rugged
- Long life — solid state reliability
- Radiant angle 8°/20°

Package Dimension



Recommended stencil size

| Part NO. | Chip Material | Lens Color |
|-------------------------|---------------|-------------|
| SL-T3020IRC050-L236-A-S | AlGaAs/Si | Water Clear |

Notes:

- All dimensions are in millimeters.
- Tolerance is ±0.10mm unless otherwise noted.

Absolute Maximum Ratings at Ta=25

| Parameter | MAX. | Unit |
|---|-------------------------|------|
| Power Dissipation | 180 | mW |
| Continuous Forward Current | 100 | mA |
| Peak Forward Current ^{*2} | 1000 | mA |
| Reverse Voltage | 5 | V |
| Electrostatic Discharge (HBM) ^{*3} | 4000 | V |
| Moisture Sensitivity Level ^{*1} | 4 | |
| Operating Temperature | -40 to + 85 | |
| Storage Temperature | -40 to + 100 | |
| IR Reflow Temperature | 260 for 10 Seconds MAX. | |

1. Storage and operating:

- (1). Storage requirements before vacuum bag opened: Temperature<30 , Humidity<65%RH;
- (2). Check air leakage and vacuum bag damage before opened. If there is any issue found, check the humidity indicator card immediately after bag opened:
 - a. If color changes on “10% circle” of the humidity indicator card only and not the circles of 20% and above, components can be used without additional handling;
 - b. If color changes on both 10% and 20% circles but not the circles of 30% and above, components must be dehumidified according to the conditions of bullet (5);
 - c. If color changes on 10%, 20%, and 30% circle or above, the product should be returned to the supplier for high temperature dehumidification;
- (3). After bag opened, manual soldering or reflow process must follow the following requirements:
 - a. Complete soldering / reflow within 72 hours;
 - b. Requirements of working environment: Temperature<30 , Humidity<60%RH;
- (4). If the working condition is outside (3)a requirement, the components must be dehumidified according to the conditions of bullet (5);
- (5). Low temperature dehumidification: temperature 60±5 , at least 24 hours;
- (6). Shelf life: 180 days. If it's over 180 days from the production date on the package label, the components must be dehumidified according to the condition of bullet (5). If customer is unable to dehumidify, return components to LIGHT for dehumidification.


2. Peak Forward Current:

Condition for is IFP pulse: Pulse Width 100µs and duty 1%.

3. Caution in ESD:

Static Electricity and surge damages the LED. It is recommend to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

LIGHT



Radiant Intensity Bin Code (IF=50mA)

| BIN CODE | Min. (mW/sr) | Max. (mW/sr) |
|----------|--------------|--------------|
| 31 | 22 | 26 |
| 32 | 26 | 31.9 |
| 33 | 31.9 | 37 |
| 34 | 37 | 44 |
| 35 | 44 | 53 |

NOTE: The I_e guarantee should be added $\pm 15\%$ tolerance.

Label Explanation


LIGHT Universal Label

| | |
|----------------------------|----------|
| LIGHT | |
| Light Electronics CO., LTD | |
| MODEL NAME: _____ | LOT NO.: |
| QUANTITY: _____ | |
| BIN: _____ | |
| PACKING DATE: _____ | |
| REMARKS: _____ | |

Customer Defined Label

| | |
|----------------------------|----------|
| LIGHT | |
| Light Electronics CO., LTD | |
| MODEL NAME: _____ | LOT NO.: |
| QUANTITY: _____ | |
| BIN: _____ | |
| PACKING DATE: _____ | |
| CUSTOMER P/N: _____ | |

Reel Dimensions



SL-T302



TABLE

